

Welded Mesh Panel Fence

3D panels for gardens and industry, 2D double-wire for stiffer runs and 358 anti-climb mesh for high-security sites. Produced together with our group brand Porçit.



Standard specification

3D panels	4–5 mm wire, 50 × 200 mm mesh, 630–2430 mm high
2D double-wire	6/5/6 and 8/6/8 mm
358 security	76.2 × 12.7 mm aperture, 4 mm wire
Panel width	2500 mm
Finish	Galvanized plus powder coat
Colours	RAL 6005, 7016, 9005

Indicative dimensions. The final specification is confirmed in your quotation.

Styles in this range



3D Welded Mesh Panels

Welded mesh panels with V-bends for stiffness. The standard perimeter fence for industry and public sites.

4 or 5 mm wire · Heights 630–2430 mm · Posts and clamps included



2D Double-Wire Panels

Flat panels with double horizontal wires for a stiffer, straighter run.

6/5/6 or 8/6/8 mm · 2500 mm panel width · Galvanized and powder coated



358 Anti-Climb Security Mesh

Narrow-aperture mesh that leaves no finger or toe hold. For high-security perimeters.

76.2 × 12.7 mm aperture · Anti-climb and anti-cut · Security fixings

Standard colours




Black
RAL 9005



Bronze
Textured bronze



Anthracite
RAL 7016



White
RAL 9016



Moss green
RAL 6005

Polyester powder coat over a pretreated surface. Other RAL colours on volume orders. Request a physical sample for colour approval.

Request a quotation

Send product, height, colour, quantity or run length, gate openings and delivery country to info@porfence.com or WhatsApp **+1 647 801 2092**. Quotes are given FOB Türkiye, CIF or DDP to the US and Europe.